



**IC-F3002** (VHF)  
**IC-F4002** (UHF)

## VHF AND UHF TRANSCEIVERS

# 5 W Output Power Also in UHF, 1500 mW Loud Audio

### Simple operation for instant communication

The IC-F3002 series is so easy to use there's no special training required. The few knobs and buttons are generously sized for easy operation and are designed to provide non-slip, positive action – even while wearing gloves.

### Easy to hear in noisy areas

The radio provides 1500 mW\* loud and clear audio with Icom custom high power handling capacity speaker. Clear communication is available even in noisy environments.

\* Typical with internal speaker

### Longer operating time

A new high efficiency FET of the IC-F3002 series reduces consumption current and provides up to 31 hours\* of operating time with the BP-299, 3150 mAh (typical) supplied battery pack.

\* TX: RX: Standby=5: 5: 90. Power save function ON.

### Weather resistant, dust protection, military rugged

While the radio is a compact unit with a height of only 111 mm, the radio is tested to dust protection and water resistant equivalent to IP54 and 11 categories of MIL-STD-810 environmental tests. In short, the IC-F3002 series is built rugged!

### Internal VOX capability for hands-free operation

The radio has the internal VOX capability for hands-free operation. Optional compatible headset with plug adapter cable OPC-2004LA can be used with the radio. Also, the VOX gain and VOX delay time are adjustable.

### Selective calling, quiet stand-by and more

2-Tone and 5-Tone signaling gives you selective calling, quiet stand-by and other convenient functions with programming. The radio "stun" function disables a radio over the air and the "revive" function restores the stunned radio.

### Scan features

The priority scan allows you to monitor one or two priority channels while scanning other non-priority channels. The TX channel and talk back functions allow you to make a quick response while scanning.

### Other features


- DTMF autodial
- CTCSS/DTCS encoder/decoder
- BLS PTT ID transmission
- MDC PTT ID and emergency
- Low battery alert
- 2-step power save
- PC programmable
- Time out timer
- Talk around function
- Lone worker function
- Enhanced emergency
- 3-color LED
- Surveillance function



Dust Protection



Water Resistance



Limited functions.

## SPECIFICATIONS

	IC-F3002	IC-F4002
GENERAL		
Frequency coverage	136–174 MHz	400–470 MHz
Number of channels	16 channels	
Type of emission	8K50F3E/14K0F3E/16K0F3E	
Channel spacing	12.5/20/25 kHz	
Power supply requirement	7.2 V DC	
Current drain (approximate)		
TX High	1.3 A	1.6 A
RX Max. audio	500 mA (Internal SP)	500 mA (Internal SP)
Standby	75 mA	70 mA
Antenna impedance	50 Ω	
Operating temperature range	–25°C to +55°C (Radio only)	
Dimensions (W × H × D) (Projections not included)	58 × 111 × 35.5 mm (With BP-299)	
Weight (approx.)	272 g (With BP-299)	
TRANSMITTER		
Output power (at 7.2 V DC)	5 W, 2 W, 1 W (Hi, L2, L1)	
Max. frequency deviation	± 5.0 kHz/±4.0 kHz/±2.5 kHz (Wide/Middle/Narrow)	
Frequency stability	±2.5 ppm	
Spurious emissions	0.25 μW (≤ 1 GHz) 1.0 μW (> 1 GHz)	
Residual modulations	58/56/53 dB typical (Wide/Middle/Narrow)	53/51/48 dB typical (Wide/Middle/Narrow)
Audio harmonic distortion (AF 1kHz 40% deviation)	1.0%/1.0%/1.5% typical (Wide/Middle/Narrow)	
Ext. microphone connector	3-conductor 2.5 (d) mm (1/16")/2.2 kΩ	
RECEIVER		
Sensitivity (at 20 dB SINAD)	–4 dBμV typical emf	
Adjacent channel selectivity	78/78/70 dB typical (Wide/Middle/Narrow)	73/73/65 dB typical (Wide/Middle/Narrow)
Spurious response rejection	70 dB minimum	
Intermodulation rejection	65 dB minimum	
Hum and noise (With CCITT filter)	57/55/51dB typical (Wide/Middle/Narrow)	52/50/47 dB typical (Wide/Middle/Narrow)
Audio output power		
Internal SP (With 8 Ω load)	1500 mW typical (at 5% distortion)	
External SP (With 8 Ω load)	400 mW typical (at 5% distortion)	
Ext. speaker connector	2-conductor 3.5 (d) mm (1/8")/8 Ω	

Measurements made in accordance with EN 300-086.

All stated specifications are subject to change without notice or obligation.

## Applicable U.S. Military Specifications &amp; IP Rating

Standard	MIL 810G	
	Method	Procedure
Low Pressure	500.5	I, II
High Temperature	501.5	I, II
Low Temperature	502.5	I, II
Temperature Shock	503.5	I-C
Solar Radiation	505.5	I
Rain Blowing/Drip	506.5	I, III
Humidity	507.5	II
Salt Fog	509.5	–
Dust Blowing	510.5	I
Vibration	514.6	I
Shock	516.6	I, IV

Also meets equivalent MIL-STD-810-C, -D, -E and -F.

Ingress Protection Standard	
Dust & Water	IP54 (Dust-protection and water resistant)


## Supplied accessories:

- Battery pack, BP-299
- Desktop charger, BC-240
- AC adapter, BC-242
- Belt clip, MB-124
- Antenna


## OPTIONAL ACCESSORIES

Some accessories may not be available in some countries. Please ask your dealer for details.

BATTERY PACK and BATTERY CASE



BP-299





BP-263

Battery pack type		Capacity	Operating time*	
BP-299	Li-ion	3050 mAh (min.)	VHF	31.4 hrs.
		3150 mAh (typ.)	UHF	29.4 hrs.
BP-263	AA (LR6) × 6	—	—	



\* TX: RX: Standby = 5: 5: 90. Power save function ON.

\* TX: RX: Standby = 5: 5: 90. Power save function ON.


RAPID CHARGER	MULTI-CHARGER
	
BC-242	BC-240
Charges the BP-299 in 4.6 hours (approx.). The BC-242 is supplied with the BC-240.	

\* The AD-139 charger adapters and BC-157S AC adapter are supplied with the BC-214N, depending on the charger version.

SPEAKER-MICROPHONES	CIGARETTE LIGHTER CABLE & POWER SUPPLY CABLES
	
HM-158LA	HM-159LA
CP-23L For use with BC-240	
OPC-515L For use with BC-240	
OPC-656 For use with BC-214N	

HEADSETS	PTT SWITCH CABLE & PLUG ADAPTER CABLE
	
HS-94	HS-95
Earhook type*	Behind-the-head type*
HS-97	Throat type*
VS-4LA For manual PTT operation	
OPC-2004LA For VOX operation	

\*2 Either the VS-4LA or OPC-2004LA is required for use with the HS-94, HS-95 or HS-97.

BELT CLIP	STANDARD ANTENNAS	STUBBY ANTENNAS
	<ul style="list-style-type: none"> <li>• FA-SC25V : 136–150 MHz</li> <li>• FA-SC55V : 150–174 MHz</li> <li>• FA-SC25U : 400–430 MHz</li> <li>• FA-SC57U : 430–470 MHz</li> </ul>	<ul style="list-style-type: none"> <li>• FA-SC56VS : 150–162 MHz</li> <li>• FA-SC57VS : 160–174 MHz</li> <li>• FA-SC73US : 450–490 MHz</li> </ul>
MB-124		
Alligator type		
Same as supplied.		

## CUT ANTENNAS

- FA-SC61VC : 136–174 MHz
- FA-SC61UC : 380–520 MHz

Icom, Icom Inc. and Icom logo are registered trademarks of Icom Incorporated (Japan) in Japan, the United States, the United Kingdom, Germany, France, Spain, Russia, Australia, New Zealand and/or other countries. All trademarks are the properties of their respective holders.

Icom Inc.

1-1-32, Kamiminami, Hirano-Ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 Fax: +81 (06) 6793 0013

[www.icomjapan.com](http://www.icomjapan.com)

Icom America Inc.  
[www.icomamerica.com](http://www.icomamerica.com)

Icom (Europe) GmbH  
[www.icomeurope.com](http://www.icomeurope.com)

Icom (Australia) Pty. Ltd.  
[www.icom.net.au](http://www.icom.net.au)

Your local distributor/dealer:

Icom Canada  
[www.icomcanada.com](http://www.icomcanada.com)

Icom Spain S.L.  
[www.icomspain.com](http://www.icomspain.com)

Shanghai Icom Ltd.  
[www.bjicom.com](http://www.bjicom.com)

Icom Brazil  
E-mail: [sales@icombrasil.com](mailto:sales@icombrasil.com)

Icom (UK) Ltd.  
[www.icomuk.co.uk](http://www.icomuk.co.uk)

Icom France s.a.s.  
[www.icom-france.com](http://www.icom-france.com)