



**IC-F1000** Series  
**IC-F2000** Series

**VHF AND UHF TRANSCEIVERS**

## Little Radio, Big Sound! Class Leading 1500 mW Audio and Full of Great Features

The IC-F1000/F2000 series provides class leading 1500 mW loud and clear audio with Icom custom high power handling capacity speaker. It offers a compact, waterproof durable design and is full of great features such as motion/stationary detection sensor, man down, voice scrambler and voice announcement functions. The radio is ideal for business and industry users who require economical value and reliability in a radio.

**Icom custom high power handling capacity speaker for 1500 mW powerful audio**

**Compact, waterproof durable design (IP67 and MIL-STD-810-G)**

**Enhanced emergency safety with built-in motion/stationary detection sensor**

**128 channel capacity with eight zones (Simple type and ten-key type)**

**Built-in 2-Tone, 5-Tone, CTCSS and DTCS**

**MDC and BIIS compatible**

**16-code inversion voice scrambler**

**Man down and lone worker functions**

**Channel announcement**

**Up to 14 hours of operating time with supplied BP-279 battery**

**5 W (VHF), 4 W (UHF) RF output power**



IC-F1000T

IC-F2000S

IC-F1000

**FEATURES****General Features**

- 136–174, 335–380, 400–470, 450–512, 450–520 MHz versions
- 1500 mW large volume audio from Icom custom speaker
- Improved sound clarity
- Compact (52.2 × 111.8 × 24.5 mm; 2.1 × 4.4 × 1.0 in) and lightweight (240 g; 8.5 oz with BP-279)
- IP67 waterproof and dust-tight protection
- Tested to 12 categories of MIL-STD-810-G environmental tests
- DTMF autodial memories
- 16-position rotary selector and ON/OFF volume knob
- “Shift key” function increases number of programmable key assignments
- Up to 14 hours of operating time with supplied BP-279 battery pack
- Eight character alphanumeric display (Ten-keypad/simple-keypad versions)
- Three color LED



1500 mW powerful audio



Icom custom high power handling capacity speaker



Waterproof for 30 minutes at one meter

**Signaling Functions**

- CTCSS and DTCS tone
- 2-Tone and 5-Tone
- MDC PTT ID, Emergency (TX/RX), Radio Check (RX), Stun (RX), Revive (RX)  
Up to 100 ID numbers and names can be saved to show the alias name, instead of the ID number
- BIIS PTT ID transmission

**Safety and Security**

- 16-code inversion voice scrambler
- Radio Stun/Revive/Kill commands (2-Tone and 5-Tone, RX only)
- Radio Stun/Revive commands (MDC, RX only)
- Auto TX function (2-Tone and 5-Tone)
- MDC emergency call with open microphone function (MDC, RX only)
- Man down function
- Lone worker function
- Motion and stationary detection function
- Surveillance function temporarily turns OFF the beep and LED indicator
- Power ON password (for the simple type and 10-key type)
- Emergency key for emergency call

**Scan Functions**

- Priority scan monitors one or two priority channels while scanning non-priority channels
- Mode dependent scan automatically changes the scan list according to the operating channel
- Power ON scan function
- Talk back timer

**Voice/Audio Functions**

- Channel announcement function
- VOX function for hands-free operation
- Audio compander
- Siren sound for security alarm

## SPECIFICATIONS

## IC-F1000 • IC-F2000 Series

	IC-F1000T/S	IC-F1000	IC-F2000T/S	IC-F2000
<b>GENERAL</b>				
Frequency coverage* (* Varies according to version)	136–174 MHz		400–470 MHz (ALL) 450–512 MHz (USA) 450–520 MHz (EXP)	335–380 MHz (EXP) 400–470 MHz (ALL) 450–512 MHz (USA) 450–520 MHz (EXP)
Number of channels	128 channels/ 8 zones	16 channels	128 channels/ 8 zones	16 channels
Type of emission* (* Depending on version)	16K0F3E*1/11K0F3E (USA/EXP) 16K0F3E/14K0F3E/8K50F3E (EUR)			
Power supply requirement	7.5 V DC nominal			
Current drain (approx.)	1.3 A			
	Tx	500 mA /77 mA (Max. audio (internal SP)/Standby)		500 mA /80 mA (Max. audio (internal SP)/Standby)
Rx				
Antenna impedance	50 Ω			
Operating temperature range	–30°C to +60°C; –22°F to +140°F (Radio specification) (USA/EXP) –25°C to +55°C (Radio specification) (EUR)			
Dimensions (W × H × D; Projections not included)	52.2 × 111.8 × 24.5 mm; 2.1 × 4.4 × 1.0 in (With BP-279)			
Weight (approx.)	240 g; 8.5 oz (With BP-279)			
<b>TRANSMITTER</b>				
Output power (Hi, L2, L1)	5 W, 2 W, 1 W		4 W, 2 W, 1 W	
Maximum frequency deviation	± 5.0 kHz (@ 25 kHz), ±4.0 kHz (@ 20 kHz), ±2.5 kHz (@ 12.5 kHz)			
Spurious emissions	70 dB minimum (USA/EXP) 0.25 μW (≤ 1 GHz), 1.0 μW (> 1 GHz) (EUR)			
Frequency stability	±2.5 ppm			
Audio harmonic distortion	1.0% typical (@ 25/20 kHz), 1.5% typical (@ 12.5 kHz) (at AF 1 kHz 40% deviation)			
FM Hum and Noise (without CCITT filter)	46 dB typical (@ 25 kHz), 40 dB typical (@ 12.5 kHz) (USA/EXP)			
Residual modulations (with CCITT filter)	50 dB typical (@ 25 kHz), 47 dB typical (@ 20 kHz), 44 dB typical (@ 12.5 kHz) (EUR)		53 dB typical (@ 25 kHz), 51 dB typical (@ 20 kHz), 48 dB typical (@ 12.5 kHz) (EUR)	
External microphone connector	3-conductor 2.5 (d) mm (1/10)/2.2 kΩ			
<b>RECEIVER</b>				
Sensitivity	0.25 μV typical			
	(at 12 dB SINAD)	–4 dBμV typical emf		
Adjacent channel selectivity	76 dB typical (@ 25 kHz), 53 dB typical (@ 12.5 kHz) (TIA-603D)		73 dB typical (@ 25 kHz), 56 dB typical (@ 12.5 kHz) (TIA-603D)	
	78 dB typical (@ 25 kHz), 71 dB typical (@ 12.5 kHz) (TIA-603A)		74 dB typical (@ 25 kHz), 64 dB typical (@ 12.5 kHz) (TIA-603A)	
Spurious response rejection	76 dB typ. (@ 25 kHz), 72 dB typ. (@ 20 kHz), 53 dB typ. (@ 12.5 kHz) (EUR)		73 dB typ. (@ 25 kHz), 73 dB typ. (@ 20 kHz), 56 dB typ. (@ 12.5 kHz) (EUR)	
	70 dB minimum			
Intermodulation rejection	74 dB typical (USA/EXP)		73 dB typical (USA/EXP)	
	68 dB typical (EUR)		67 dB typical (EUR)	
Hum and noise	(With CCITT filter)		49 dB typical (@ 25 kHz), 43 dB typical (@ 12.5 kHz) (USA/EXP)	
	(Without CCITT filter)		52 dB typical (@ 25 kHz), 49 dB typical (@ 20 kHz), 46 dB typical (@ 12.5 kHz) (EUR)	
AF output power (at 5% distortion)	1500 mW typical (With 8 Ω load)			
	Internal SP	400 mW typical (With 8 Ω load)		
External speaker connector	2-conductor 3.5 (d) mm (1/8)/8 Ω			

All stated specifications are subject to change without notice or obligation. Measurements made in accordance with TIA-603 (USA/EXP) or EN 300-086 (EUR).

\*1 25 kHz bandwidth is no longer available for FCC Part 90 licensees for USA versions.

## Applicable U.S. Military Specifications &amp; IP Rating

Standard	MIL 810G		
	Method		Procedure
Low Pressure	500.5		I, II
High Temperature	501.5		I, II
Low Temperature	502.5		I, II
Temperature Shock	503.5		I-C
Solar Radiation	505.5		I
Rain Blowing/Drip	506.5		I, III
Humidity	507.5		II
Salt Fog	509.5		–
Dust Blowing	510.5		I
Immersion	512.5		I
Vibration	514.6		I
Shock	516.6		I, IV

Also meets equivalent MIL-STD-810-C, -D, -E and -F.

## Ingress Protection Standard

Dust & Water IP67 (Dust-tight and waterproof protection)

## Battery Life

Battery pack	Type	Capacity	Operating time*
BP-278	Li-ion 7.2 V	1190 mAh (typ.), 1130 mAh (min.)	Up to 10 hours
BP-279	Li-ion 7.2 V	1570 mAh (typ.), 1485 mAh (min.)	Up to 14 hours
BP-280	Li-ion 7.2 V	2400 mAh (typ.), 2280 mAh (min.)	Up to 20 hours

\* TX: RX: standby = 5:5:90. Power save function ON.

**Supplied accessories:** (May differ or not supplied, depending on version)  
 • Battery pack, BP-279 • Desktop charger, BC-213\* • Belt clip, MB-133  
 • AC adapter, BC-123SA/SE/SUK or BC-242\* • Antenna



The "3D GENUINE Icom label" is attached to the rear chassis under the battery. Check the Icom website for details: <http://www.icom.co.jp/world/genuine-info/>

### BATTERY PACKS

**BP-278:** 1190 mAh (typ.), 1130 mAh (min.) rechargeable Li-ion battery.  
**BP-279:** 1570 mAh (typ.), 1485 mAh (min.) rechargeable Li-ion battery.  
**BP-280:** 2400 mAh (typ.), 2280 mAh (min.) rechargeable Li-ion battery.



BP-278 BP-279 BP-280

### BATTERY CHARGERS

**BC-213:** Desktop charger.  
 Charges the BP-278, BP-279 or BP-280. Charges the BP-279 in 2.5 hours (approximate).  
 + **BC-123SA/SE/SUK/SV** or **BC-242:** AC adapter.

**BC-214:** Multi-charger.  
 Charges up to six radios and/or batteries at the same time.  
 + **BC-157S:** AC adapter.

\* AD-130 charger adapter is supplied with the BC-214, depending on version.



BC-213 BC-123SA BC-214 BC-157S

### POWER SUPPLY CABLES AND CHARGER BRACKET

**CP-23L:** Vehicle charger cable for use with the BC-213.  
**OPC-656:** DC power cable for use with the BC-214.  
**MB-130:** Charger bracket for use with the BC-213.



CP-23L OPC-656 MB-130

### SPEAKER-MICROPHONES

**HM-168LWP:** Waterproof speaker microphone with a waterproof connector. IP67 protection.  
**HM-158LA:** Compact speaker microphone with 3.5 mm earphone jack.  
**HM-159LA:** Speaker microphone with 3.5 mm earphone jack.



HM-168LWP HM-158LA HM-159LA

### EARPHONE-MICROPHONES

**HM-153LA:** Durable lapel microphone with earphone.  
**HM-166LA:** Light weight lapel microphone with earphone.



HM-153LA HM-166LA

### HEADSETS, PTT SWITCH CABLE & PLUG ADAPTER

**HS-94LWP:** Earphone-headset with a waterproof connector.  
**HS-95LWP:** Behind-the-head headset with a waterproof connector.  
**HS-94:** Earphone-headset. (Use with either the VS-4LA or OPC-2004LA)  
**HS-95:** Behind-the-head headset. (Use with either the VS-4LA or OPC-2004LA)  
**HS-97:** Throat microphone. (Use with either the VS-4LA or OPC-2004LA)  
**VS-4LA:** PTT switch cable for manual PTT operation.  
 (For use with either the HS-94, HS-95 or HS-97)  
**OPC-2004LA:** Plug adapter cable for VOX operation.  
 (For use with either the HS-94, HS-95 or HS-97)



HS-94LWP HS-95LWP HS-97 VS-4LA OPC-2004LA

### BELT CLIP

**MB-133:** Alligator belt clip. Same as supplied.



MB-133

### SOFTWARE AND CABLE

**CS-F2000:** Programming software.  
**OPC-478UC:** USB type radio programming cable.

### ANTENNAS

**FA-SC25V:** 136–150 MHz  
**FA-SC28V:** 148–162 MHz  
**FA-SC29V:** 160–174 MHz  
**FA-SC55V:** 150–174 MHz  
**FA-SC25U:** 400–430 MHz  
**FA-SC57U:** 430–470 MHz  
**FA-SC72U:** 470–520 MHz  
**FA-SC02U:** 330–380 MHz



FA-SC72U

### HIGH GAIN ANTENNAS

**FA-SC62V:** 150–160 MHz  
**FA-SC63V:** 155–165 MHz



FA-SC62V FA-SC63V

### STUBBY ANTENNAS

**FA-SC26VS:** 136–144 MHz  
**FA-SC27VS:** 142–150 MHz  
**FA-SC56VS:** 150–162 MHz  
**FA-SC57VS:** 160–174 MHz  
**FA-SC26US:** 400–450 MHz  
**FA-SC73US:** 450–490 MHz



FA-SC26VS FA-SC27VS FA-SC56VS



FA-SC57VS FA-SC26US FA-SC73US

### CUT-TYPE ANTENNAS

**FA-SC61VC:** 136–174 MHz  
**FA-SC61UC:** 380–520 MHz



FA-SC61VC FA-SC61UC

Some options may not be available in some countries. Please ask your dealer for details.

Icom, Icom Inc. and the Icom logo are registered trademarks of Icom Incorporated (Japan) in Japan, the United States, the United Kingdom, Germany, France, Spain, Russia, Australia, New Zealand and/or other countries. All other trademarks are the properties of their respective holders.

Icom Inc. 1-1-32, Kamiminami, Hirano-Ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 Fax: +81 (06) 6793 0013

[www.icom.co.jp/world](http://www.icom.co.jp/world) **Count on us!**

Icom America Inc.  
[www.icomamerica.com](http://www.icomamerica.com)

Icom (Europe) GmbH  
[www.icomeurope.com](http://www.icomeurope.com)

Icom (Australia) Pty. Ltd.  
[www.icom.net.au](http://www.icom.net.au)

Your local distributor/dealer:

Icom Canada  
[www.icomcanada.com](http://www.icomcanada.com)

Icom Spain S.L.  
[www.icomspain.com](http://www.icomspain.com)

Shanghai Icom Ltd.  
[www.bjicom.com](http://www.bjicom.com)

**Radiostanice.cz**  
 RCS Brno - radiostanice.cz, a.s.  
 Stránského 1350/35, 616 00 Brno  
 ☎ +420 548 216 942  
 ✉ [obchod@radiostanice.cz](mailto:obchod@radiostanice.cz)

Icom Brazil  
 E-mail: [sales@icombrasil.com](mailto:sales@icombrasil.com)

Icom (UK) Ltd.  
[www.icomuk.co.uk](http://www.icomuk.co.uk)

Icom France s.a.s.  
[www.icom-france.com](http://www.icom-france.com)